

4184 E. Conant St. Long Beach, CA 90808 Tel. 888-900-1002 Fax. 310-900-1088 www.turboairinc.net

| Project : | |
|------------|------|
| Model #: | |
| Item #: | Qty: |
| Approval : | |

Unit Cooler

Model: LED082B



- Blue anti-corrosion-fin increases the life span of the coil.
- Air-pass guard is located at the bottom of the coil to improve heat exchange rate.
- Easy to replace defrost heater. (LED model)
- Corrugated fin is used to increase heat exchanges rate by expanding the surface area.
- Even in confined space, all parts can be reached easily by opening the front cover.
- Location of power connector makes replacement of motor convenient.
- Seamless inner groove copper tube increases the heat exchange rate by reducing the space between the fin and copper tube.
- Venturi type distributor and precise orifice hole are used to minimize the pressure drop and maximize the freezing capacity respectively.
- Even in confined space, all parts can be reached easily by opening the front cover.

- Thermostat is installed to prevent over temperature on heater.
- Circuit opens automatically over 50°F.
- Parts available :

Expansion Valve (Sporlan) (Pre Mounted) Solenoid Valve (Sporlan) Thermostat (Johnson Control)

- The spiral fan guard enables cold air to be delivered efficiently and thoroughly.
- The protruding fan and motor placement substantially reduce vibration and noise.
- PSC fan motor, which prevents oil evaporation, is used for long life expectancy.
- EC Motor (optional) for high energy efficiency.
- Unique air flow system (patent pending) results in improved circulation within crowded walk-in cooler/freezer.
- Anti-oxidizing stainless steel mounting and bolts.









Unit Cooler

Model: LED082B

LED ELECTRIC DEFROST MODELS 60HZ. WITH PSC MOTORS.

| Capacity BTUH/Watts | Fan Data | | |
|-----------------------------------|----------|-----|--|
| 10°F /6°C TD -20°F / -29°C SST | CFM/m³H | No. | |
| 8230 | 1300 | 2 | |


| EC Motor Data | | | Defrost Heater | | |
|---------------|---------------|-------|----------------|---------------|---------------|
| | 230V 1Ph 60Hz | | | (Total Amps) | |
| НР | Total Amps | Watts | Watts | 230 / 1/60 | 230 / 3/60 |
| 1/15 | 0.70 | 160 | 1800 | 7.80 | 4.50 |

| | Approx. | | | |
|---------------|---------|-----------------------|---------|----------------|
| Coil Inlet | Suction | External Equalizer | Drain | Net Wt. Lbs |
| 1/2 OD | 5/8 ID | 1/4 OD | 3/4 MPT | 51 |


Design and specifications subject to change without notice


■ WARRANTY: 1 Year Fan Motor and Parts Warranty

PLAN VIEW (unit: inch)



FRONT VIEW





SIDE VIEW



■ **Toll Free**: 888-900-1002









