

4184 E. Conant St. Long Beach, CA 90808 Tel. 888-900-1002 Fax. 310-900-1088 www.turboairinc.net

| Project |
|---------|
|---------|

Item # :

Model # :

÷

Qty:

Approval :

# **Condensing Unit**

## Model : TS050MR404A3-T





## \_\_\_\_ FEATURES / BENEFITS \_\_\_\_

- Blue anti-corrosion-fin increases the life span of the coil.
- Seamless inner groove copper tube increases the heat exchange rate by reducing the space between the fin and copper tube.
- Highest quality compressor in the world.



- Head pressure control stabilizes the freezing of liquid line, minimizes formation of flash gas to increase efficiency of the system, and prevents compressor damage by controlling high pressure.
- Experienced engineers have designed the system for maximum efficiency.
- Fan Blades : Specifically matched with motors and coil for maximum air movement and cooling.

- Control box is designed for easy installation.
- Low pressure control is adjustable.
- All the parts are compliant with industry standards and interchangeable with readily available parts.
- Wiring : Easily accessible. Compressor comes with a wiring harness that is manufactured with connections that will not come loose with vibration.
- Control box and service valves are located outside for easy service.
- Base : Heavy duty steel. Legs are 2-1/6" tall
- Cabinet : Prepainted with galvanized body. Protects against corrosion.
- All products carry UL, cUL, ISO 9001 approvals.



### Model : TS050MR404A3-T

#### **PERFORMANCE CHART**

| PERFORMANC    | CHART     |       |       |       |       |       |       | R404A     |
|---------------|-----------|-------|-------|-------|-------|-------|-------|-----------|
|               | 40°F(SST) | 30°F  | 25°F  | 20°F  | 15°F  | 10°F  | 0°F   | -10°F     |
| 90'F(AMBIENT) | 61600     | 51000 | 46850 | 43000 | 39170 | 35280 | 28140 | 22080     |
| 95'F          | 58700     | 48530 | 44580 | 41000 | 37320 | 33580 | 26740 | 21420     |
| 100'F         | 55700     | 46080 | 42280 | 38850 | 35390 | 31850 | 25340 | 20320     |
| 110'F         | 49700     | 40940 | 37540 | 34500 | 31450 | 28320 | 22540 | 18120     |
| _             |           |       |       |       |       |       |       | R448/449A |
|               | 40°F(SST) | 30°F  | 25°F  | 20°F  | 15°F  | 10°F  | 0°F   | -10°F     |
| 90'F(AMBIENT) | 55550     | 46610 | 42750 | 38770 | 34920 | 31500 | 25280 | 19160     |
| 95'F          | 53300     | 44740 | 41050 | 37220 | 33760 | 30460 | 23940 | 17900     |
| 100'F         | 51500     | 43220 | 39325 | 35670 | 32320 | 29160 | 23020 | 17100     |
| 110'F         | 47270     | 39800 | 36565 | 32880 | 29520 | 26560 | 20780 | 15100     |

#### **SPECIFICATION**

|                            | TS050MR404A3-T                |  |
|----------------------------|-------------------------------|--|
| Compressor                 | ZB38KQE-TF5                   |  |
| Line Size                  | 1/2" Liquid 1-1/8" Suction    |  |
| Refrigerant (Receiver 90%) | 20 lbs                        |  |
| Fan Data                   | 1Fan (3760CFM)                |  |
| Dimensions                 | 30.28(D) x 38.5(W) x 27.28(H) |  |
| Net Weight                 | 279 lbs                       |  |
| Power Supply               | 208-230/3ph/60hz              |  |
| Compressor Amp             | 22.1(RLA), 128(LRA)           |  |
| MCA/MOPD                   | 29.8/50                       |  |
| Sound dBA                  | 72                            |  |

Design and specifications subject to change without notice

WARRANTY : <sup>1</sup> Year Compressor Warranty (4 Year extended warranty available)
1 Year Fan Motor and Parts Warranty

#### **PLAN VIEW**

