

Project:	
Model #:	
Item #:	
Available W/H:	Qty:
Approval:	
AIA #:	SIS #:
CSI Section 11400	

## Solid Door Heated Cabinet - Universal Tray Slide

Reach-In  
M3 Series

**Model : M3H24-1-TS**

### FEATURES & BENEFITS

- **Digital temperature control & monitor system**

  - Keeps food products safe by maintaining constant temperatures
  - Alarm beeps when doors are not sealed
  - Digital display allows for easy monitoring
- **Ducted fan air distribution system**

Maintains temperature within the food zone
- **On/Off switch**

ON/OFF switch is located on control panel
- **Stainless steel cabinte construction**

The Turbo Air M3 heated cabinet model boasts a stainless steel exterior (galvanized steel top, bottom and back) and interior. It guarantees the utmost in cleanliness and long product life. Sharp corners and edges have been rounded to reduce the risk of injury. The M3 adds a touch of style to the most refined setting.
- **LED interior lighting**
- **High-density polyurethane insulation**

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- **Field reversible door hinge**
- **Stainless steel universal tray slides standard**

Each tray slide accommodates up to 6" deep full size pan or 18" x 26" size pan or 14" x 18" size pans or 12" x 20" size pans.
- **Heated cabinet holds 140°F ~ 180°F for the best in food preservation**



Model	Swing Door	CU./FT.	#of Tray slides (pairs)	Wattage (W)	AMPS	Crated Weight (lbs.)	L x D x H† (inches)
<b>M3H24-1-TS</b>	<b>1</b>	<b>22.7</b>	<b>5</b>	<b>950</b>	<b>8.5</b>	<b>231</b>	<b>28<sup>3</sup>/<sub>4</sub> X 30<sup>3</sup>/<sub>4</sub> X 78</b>

# Solid Door Heated Cabinet - Universal Tray Slide

Reach-In  
M3 Series

## Model : M3H24-1-TS

ELECTRICAL DATA	
Voltage	115/60/1
Plug Type	 NEMA 5-15P
Full Load Amperes	8.5
Wattage (W)	950
Cord Length (ft.)	8
DIMENSIONAL DATA	
# of Doors	1
Net Capacity (cu. ft.)	22.7
Ext. Length Overall (in.)	28 3/4 (730mm)
Ext. Depth Overall (in.)	30 3/4 (780mm)
Ext. Height Overall (in.)†	78 (1981mm)
Int. Length Overall (in.)	22 3/8 (568mm)
Int. Depth Overall (in.)	24 5/8 (625mm)
Int. Height Overall (in.)	58 3/4 (1493mm)
# of Tray slides (pairs)	5
Net Weight (lbs.)	188
Gross Weight (lbs.)	231

Design and specifications subject to change without notice.  
Actual shipping weight may differ due to extra packing materials for product protection.  
† Height does not include 5" for caster height.

### ■ WARRANTY : 3 Year Parts and Labor Warranty

### ■ STANDARD FEATURES

- Door lock
- 4" dia. swivel casters with locks on the front set
- Easy replaceable one piece magnetic door gaskets
- Solid and sturdy grille design


\*\* Lead time applies. Please contact your sales representative for more details to order.

### ■ OPTIONAL ACCESSORIES


- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- 6" stainless steel leg: 30221M0600
- Additional universal tray slides (1 pair): T24H139080

## PLAN VIEW

(unit : inch)



TOP VIEW



SIDE VIEW

Ver.20260130



ENERGY STAR®  
Qualified

- Turbo Air: 800-627-0032
- Bake Tech Innovation: 800-500-3519
- Warranty: 800-381-7770
- AC: 888-900-1002