

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
tem #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Model : TST-28SD-12-D2-FB-N

Mega Top Unit - Drawers / Front Breathing Airflow

Food Prep Tables - Drawers Super Deluxe Series

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily

Digital temperature control & monitor system

Keeps food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

Front Breathing airflow

Front Breathing airflow is designed to draw in air and discharge from the front, allowing units to run at high efficiency in tight spaces and eliminates the need for surrounding clearances.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior (ABS door liner) and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe adds a touch of style to the most refined setting.

Cold Bunker system

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place high density, CFC free polyurethane insulation.

- Insulated pan cover
- 9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail
- Each top drawer accommodates up to 6" deep, (2) two 1/3 size pans with (2) two 1/6 size pans or (6) six 1/6 size pans. And each bottom drawer accommodates up to 6" deep, (2) two 1/3 size pans or (4) four 1/6 size pans (drawer pans not included)



TST-28SD-12-D2-FB-N	-	2	6.5	-	12	1/6	6.6	403	271/2 x 34 x 395/8
Model	Swing Doors	Drawers	CU /FT	#of Shelves	#of Pans	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^+$

Ver.20250710 Printed in U.S.A.

* Depth does not include 3" for cutting boards. + Height does not include 4-1/2" for caster height.

Mega Top Unit - Drawers / Front Breathing Airflow

(unit : inch)

Model : TST-28SD-12-D2-FB-N

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	(i) NEMA 5-15P				
Full Load Amperes	6.6				
Compressor HP	1/6				
Cord Length (ft.)	9				
Refrigerant	R-290				
DIMENSIONAL DATA					
Ext. Length Overall (in.)	271/2 (700mm)				
Ext. Depth Overall (in.)*	34 (864mm)				
Ext. Height Overall (in.) [†]	395/8 (1006mm)				
# of Doors	-				
# of Drawers	2				
# of Shelves	-				
# of Pans	12				
# of Hood	1				
Net Capacity (cu. ft.)	6.5				
Net Weight (lbs.)	391				
Gross Weight (lbs.)	403				

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 3" for cutting boards.

+ Height does not include 4-1/2" for caster height.

• WARRANTY : 5 Year Parts and Labor Warranty 7 Year Compressor Warranty

STANDARD FEATURES

- Anti-corrosion coated evaporator
- Self-contained system
- 4" dia. swivel casters with locks on the front set
- 1/6 size, 4" deep condiment pans included

OPTIONAL ACCESSORIES

Low Profile casters kit

- (4) 1" caster (Roller Type): S28R813660
- (1) 3/8"H drain pan: SDP1Q000
- (1) Brackets for drain pan: (Left) SDP1Q000-BL, (Right) SDP1Q000-BR
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Removable food cover: RCT-28-12
- Clear lid: CL-28-12



271/2 (700mm) 261/2 (672mm)

PLAN VIEW



Ver.20250710

- **Turbo Air:** 800-627-0032 **Bake Tech**: 800-500-3519
- Warranty: 800-381-7770 AC: 888-900-1002

NATURAL Refrigerant 7 YEAR WARRANTY 5 YEAR Intertek

lurbo air

